

-
-
-
-
-
-
-
-

C++ As a Better C



C++ Object Oriented Programming
Pei-yih Ting
NTOU CS

◦ ◦ ◦ ◦ ◦ ◦ ◦ ◦ 1

Comments

◦ Comments in C++ vs. C

```
/* You can do this
   across multiple lines */
// Or you can do this on a single line
```

ends at end of line

◦ Advantages of //

- * What's the problem?
`if (b>a)
 return b; /* could be also b>=
else
 return a; /* note that we return a in case of a tie */`

missing */
- * Solution with //
`if (b>a)
 return b; // could be also b>=
else
 return a; // note that we return a in case of a tie`

◦ Rules:

- * Use // syntax for single-line comments
- * Use /*...*/ syntax for multi-line comments

3

Contents

- Comments
- User-defined type names
- Function prototypes in C++
- Function signatures
- Better I/O library
- Default function arguments
- Macros
- Inline functions
- #define vs. constant variables
- new and delete operators
- Reference variables
- Stricter typing systems

2

User-defined Type Names

◦ struct, enum, union tags are type names

- * struct:
`struct Stack {
 ...
};`
 - > C: struct Stack operatorStack;
 - > C++: Stack operatorStack;

```
typedef struct tag
{
    ...
} Stack;
Stack operatorStack;
```

- * union:
`union Value {
 int iValue;
 double dValue;
};`
 - > C: union Value field;
 - > C++: Value field;

- * enum:
`enum Color {RED, GREEN, BLUE};`
 - > C: enum Color bgColor;
 - > C++: Color bgColor;

4

Function Prototypes in C++

- Function prototypes are REQUIRED
 - Otherwise you must define the function before you use it, i.e. in Pascal-style
 - In K&R C (before ANSI C), a function *foo* used without suitable prototype has default prototype, arguments are passed with default promotion rules (i.e. 4bytes / 8bytes rule)

```
int foo();
```

void as an argument in C prototypes

- What do the following 2 prototypes differ in traditional C?

```
int foo(void);  
int foo();
```

A function foo that takes an indeterminate number of arguments

- In C++, the above two are equivalent. The second one is preferred.
- The notorious **variable argument list**, represented by ellipses (...)
 - `int printf(const char *format, ...);` C++ still keep it for compatibility

5

K&R C

Better Input/Output

- Type-aware I/O processing, mixed data types

```
int x = 5; double y = 6.0; char *s = "Hello";
```

 - C output: `printf("x=%d y=%f s=%s", x, y, s);`
 - C++ output: `cout << x << y << s;`
 - C input: `scanf("%d%f%s", &x, &y, s);`
 - C++ input: `cin >> x >> y >> s;` (no ampersand & trap)
- Header file: `iostream`
- Insertion operator: `<<`, inserts data into the output stream
- Extraction operator, `>>`, extracts data from the input stream
- Errors:
 - `cout >> age;`
 - `cin << age;`
- Mix C stdio with C++ iostream: `ios::sync_with_stdio();`
- `cerr`
- `clog`

not preferred

7

Function Signatures

- C: a function is identified completely by its name
C++: a function is identified by its signature (name, #params, types of params and const modifier)
- Ex. in C,

```
void draw(int) {}  
void draw(double) {}
```

 error: 'void __cdecl draw(int)' already has a body
in C++, both the above two are OK, compiler encodes the function name with type safe linkage rules (called *name mangling*)
- Note: Function return type is not a part of its signature
Access privilege is not a part of its signature
- C++ calls a C function: `extern "C" int func(int *, float);`
- C calls a C++ function:

```
extern "C" {  
    int fun(int *, float){....};  
}
```

 or `extern "C" int fun(int *, float){...};`

in C++ file

6

Default Function Arguments

- Function arguments can be given default (optional) values.

```
void printName(char *first, char *last, bool inverted=true);  
void main() {  
    char firstName[50] = "Joe", lastName[50] = "Smith";  
    printName(firstName, lastName);  
    printName(firstName, lastName, false);  
}  
...
```

specified only in the prototype, OK to differ in different scopes

```
void printName(char *first, char *last, bool inverted) {  
    if (!inverted)  
        cout << first << ' ' << last << '\n';  
    else  
        cout << last << ' ' << first << '\n';  
}
```
- Rules:
 - Can have any number of default arguments
 - Default arguments must come after non-default arguments, and not the other way around

Good for avoiding seldom-used parameters

8

Macros

- ◊ Preprocessor macro introduces subtle bugs if not careful

```
#define square(x) (x*x)
void main() {
    int x=5, y;
    y = square(x);
    cout << y;
}
```

Output: 25

- ◊ The problem with macros

- * The preprocessor knows nothing about C syntax or semantics
- * Cannot debug into a macro function (a macro is invisible to the compiler/debugger)

- ◊ The same macro fails on the following

```
int x=5, y=6;
cout << square(x+y);
```

Output: 41

- ◊ Corrections

```
#define square(x) ((x)*(x))
```

9

Macros (cont'd)

- ◊ Not every macro problem can be solved by parenthesizing

```
#define inverse(x) (1/(x))
double x=5;
cout << "x=" << inverse(x) << endl;
int y=5;
cout << "y=" << inverse(y) << endl;
```

Output:
x=.2
y=0

- ◊ Corrections:

```
#define inverse(x) (1.0/(x))
```

- ◊ Arguments of a macro could be evaluated more than once

```
#define square(x) ((x)*(x))
```

...

```
int x=5;
cout << "square of 5 is " << square(x++) << ", x=" << x;
```

Output:
square of 5 is 30, x=7

- ◊ There are various problems accompanying macros. They all require prudent inspections.

10

Inline Functions

- ◊ C++ has inline functions, which provide the same functionality as macros without the above drawbacks

```
inline int square(int x); // function prototype, not a macro
void main() {
    int x=5, y=6;
    cout << square(x+y);
}
inline int square(int x) { return x * x; }
```

Output: 121

```
inline double inverse(double x);
void main() {
    int x=5;
    cout << inverse(x);
}
inline double inverse(double x) { return 1 / x; }
```

Output: .2

- ◊ The compiler can only inline **simple** functions (compiler-dependent) and will IGNORE all other inline requests.

11

Declare Variables On-the-fly

- ◊ C: Local variables must be declared at the beginning of a block.

C++: Local variables can be declared anywhere inside a block, the scope extends to the end of the block.

- ◊ Ex.

```
void main() {
    int array[5] = {0, 1, 2, 3, 4};
    cout << array[0] << endl;
    ...
    int sum = 0;
    for (int i=0; i<5; i++) {
        sum += array[i];
    }
    cout << sum;
}
```

- ◊ Why should you do this? better readability
encourages single-usage variables
- * Most commonly used for temporary loop variables

12

Declare Variables On-the-fly (cont'd)

- Cannot branch over ‘a variable definition with initialization’ error

```
void main()
{
    int x;
    x = 1;
    goto test;
    int y=5;
test:
    x = 2;
    y = 10;
}
```

```
void main()
{
    int x;
    x = 1;
    goto test;
    int y;
test:
    x = 2;
    y = 5;
}
```

```
void main()
{
    int x;
    x = 1;
    goto test;
    int y=5;
test:
    x = 2;
    y = 5;
}
```

```
void main()
{
    int x=1;
    switch (x) {
        case 1:
            int y=5;
            break;
        case 2:
            y=10;
            ...
    }
}
```

Compilation OK, but better not do this, use suitable block structure instead

13

More on Constant Variables

- ‘const’ modifies the type specifier differently according to its position

```
void main()
{
    char string1[kMaxSize] = "Hello world";
    char string2[kMaxSize] = "Good bye";
    string1[0] = 'T'; // legal
    const char *ptrString1 = string1; // char is a constant, char* is not
    ptrString1[0] = 'T'; // illegal
    ptrString1++; // legal
    char *const ptrString2 = string1; // char* is a constant, char is not
    ptrString2[0] = 'T'; // legal
    ptrString2++;
    ptrString2 = string2; // illegal
    char *const ptrString3; // illegal
    const char *const ptrString4 = string1; // both char and char* are constants
}
```

15

#define vs. const

- Defines should be replaced by constant variables in C++

```
#define kMaxSize 1000 // do not do this
const int kMaxSize = 1000; // much better
int array[kMaxSize];
```

- A constant variable is a real variable, therefore, has a type that compiler can check upon, and is visible to the debugger.

- Constant arguments promise more: a const argument tells the client that the argument will not be changed and the compiler guarantees that it won’t

```
static bool isStartWithH(const char *inputString) {
    char firstLetter = inputString[0];
    firstLetter = toupper(firstLetter);
    return firstLetter == 'H';
}
```

Usually used with pointer or reference parameters

```
int size;
cin >> size;
const int kMax = size;
int array[kMax];
```

Compiler guarantees that the following won’t happen

```
static bool isStartWithH(const char *inputString) {
    inputString[0] = toupper(inputString[0]);
    return inputString[0] == 'H';
}
```

14

‘static’ modifier in C

- Different semantics with 3 types of usages:

I. global scope variable:

Identifier scope is restricted to a file

static int g_data;

II. global scope function:

static int func(int x, float y) { ... }

III. local scope variable:

int func() {

static int localData;

...

}

The life cycle of this variable extends over multiple calls of this function

- File scope variables and functions: type I and type II above

* their scopes are restricted to the file unit in which they are declared

* used in C to encapsulate a module, i.e. make that identifier local to a file

```
file1.c static int x1;
int x2;
static int func1(int x) { ... }
int func2(int x) { ... }
```

file2.c

```
int func() {
    extern int x1; int func1(int);
    func1(x1); // both undefined
    func2(x2); // OK
}
```

- In C++, these semantics remain the same. Besides, constant variables are implicitly static.

16

New Ways to Handle Memory

- ❖ C++ has better ways to allocate/deallocate memory

C	malloc	free
C++	new, new[]	delete, delete[]

- ❖ Ex.

```
int *x, *y;
int *array;
x = new int;
y = new int(40);
array = new int[100];
delete x;
delete y;
delete[] array;
```

initialization: single-value variables
(not for arrays) and objects

new and delete are built-in operators
no #include file necessary

- ❖ Why does C++ switch to these new usages?

- * Simplicity: C: array = (int *) malloc(sizeof(int)*100);
C++: array = new int[100];
- * Auto initialization and clean-up
- * Consistency with C++ object allocation

17

Handling Memory Allocation Errors

- ❖ malloc(): int *ptr=(int *) malloc(sizeof(int)*200);
if (ptr==0) printf("Memory allocation error!!");
- ❖ new: int *ptr=new int;
if (ptr==0) printf("Memory allocation error!!");
- ❖ You can also specify a function to be called in case of memory failure. **Corrective actions** such as freeing memory space can be taken automatically and the **new** operation can be retried.
- ❖ Ex.

```
static int newFailed(size_t size) {
    if (gSparePtr!=0) {
        delete [] gSparePtr; // free some spare space
        gSparePtr = 0;
        cout << "[newFailed " << size << "]";
        return 1; // request the new operator to retry
    }
    return 0; // stop retrying
}
```

19

new / delete Usages

- ❖ Errors due to unmatched allocation/deallocation

- * int *x1=new int; ... delete[] x1;
- * int *x2=new int[100]; ... delete x2;
- * int *x3=new int; ... free(x3);
- * int *x4=(int *) malloc(sizeof(int)); ... delete x4;

- ❖ Special safety checks

```
int *ptr=0;
...
if (!ptr) free(ptr); // freeing null is fatal in C/C++
delete ptr; // OK to delete null
```

- * better erase the pointer after deletion (good coding practice)
delete ptr; **ptr= 0**;

- ❖ Multi-dimensional array: (actually 1-dim data)

```
int (*xp)[3] = new int[20][3]; ... delete[] xp;
or equivalently
typedef int IARY[3]; IARY *xp=new IARY[20]; ... delete[] xp;
```

18

Handling Memory Allocation Errors

- ❖ Installing and resetting the new handler VC6.0

```
#include <new.h>
int *gSparePtr = 0;
static int newFailed(size_t size);
void main() {
    int *ptr[20], i, *spoiled;
    _PNH old_handler = _set_new_handler(newFailed);
    spoiled = new int[150000000];
    gSparePtr = new int[20000000];
}
```

```
for (i=0; i<20; i++) {
    cout << i << " ";
    ptr[i] = new int[5000000];
    cout << ptr[i] << endl;
}
```

```
_set_new_handler(old_handler);
```

}

restore the original new handler
 can also call _set_new_handler(0) to remove

```
0 28CB0020
1 29FD0020
2 2B2F0020
3 2C610020
4 2D930020
5 2EC50020
6 2FF70020
7 31290020
8 325B0020
9 338D0020
10 [newFailed 20000000]
34BF0020
11 35F10020
12 37230020
13 38550020
14 00000000
15 00000000
16 00000000
17 00000000
18 00000000
19 00000000
```

20

Handling Memory Allocation Errors

- ANSI C++ version of set_new_handler

```
#include <new>
using namespace std;
...
static void newHandler();
...
void main() {
    new_handler old_handler=set_new_handler(newHandler);
    ...
    set_new_handler(old_handler);
}
...
static void newHandler() {
}
```

In VC6.0 this does not work, because set_new_handler() is implemented as a stub function only.

21

References

- C simulates “call by reference” through pointers

```
void func(int *ptrData) {
    *ptrData = 10;
}
```

```
void main() {
    int data;
    ...
    func(&data);
    ...
}
```

- C++ has true references

```
void func(int &param) {
    param = 10;
}
```

```
void main() {
    int data;
    ...
    func(data);
    ...
}
```

no pointer dereference required

- Some C++ programmers might do the following for saving time and memory

```
void Foo(const CBigData &data) {
    ...
}
```

22

References (cont'd)

- There are no promotions or type conversions with references

```
void func(double &data) {
    data = 10;
}
```

```
void main() {
    int data;
    ...
    func(data);
    ...
}
```

error C2664: 'func' : cannot convert parameter 1 from 'int' to 'double &'

- A reference variable cannot be bound to a temporary object

```
int getValue() {
    int tmp;
    return tmp;
}
int func(int &value);
void main() {
    func(getValue());
}
```

error C2664: 'func' : cannot convert parameter 1
from 'int' to 'int &'

23

Stricter Typing System

- In C, you can do

```
int *intPtr;
void *genericPtr;
genericPtr = intPtr;
intPtr = genericPtr;
```

Giving up the advantages of strict type checking

// convert typed pointer to generic pointer
// generic to typed

- In C++,

```
int *intPtr;
void *genericPtr;
genericPtr = intPtr;           // convert typed pointer to generic pointer
intPtr = genericPtr;          // ERROR: cannot convert from 'void *' to 'int *'
intPtr = (int *) genericPtr;   // explicit type cast
```

- In C++, char literal is not treated as int as in C

```
void func(int i);
void func(char c);
```

overloaded functions

...

func('A') will invoke the second function

24

Miscellaneous

❖ Scope resolution operator

```
static int x = 10;
void main() {
    int x = 5;
    cout << x << endl;
    cout << ::x << endl;
}
```

Output:
5
10

❖ bool

- * A new type of boolean variable
- * The value can be true or false

25

Explicit Type Conversion

```
int i; float f;
...
void *vp = &i;
float *fp = static_cast<float *>(vp);
i = static_cast<int>(f);
const int i = 0;
j = const_cast<int*>(&i); // Preferred
*j = 10;
cout << "i=" << i << " *j=" << *j << endl; // weird, compiler make it 0
                                                // directly in the code
struct X { int a[100]; } x;
...
int *xp = reinterpret_cast<int *>(&x);
```

Output:
i=0 *j=10

27

Explicit Type Conversion

❖ C style type casting operator (type coercion)

```
int b = 200;
unsigned long a = (unsigned long int) b;
```

Basically commands the compiler to “forget about type checking” – introduction a hole in the C/C++ type checking system.

❖ C++ style explicit casts: (including Run-time type information, RTTI)

- * **static_cast**: for well-behaved and reasonably well-behaved casts, ex. int to float, float to int, forcing a conversion from a void*
- * **const_cast**: to cast away const or volatile, i.e. make a const variable non-const
- * **reinterpret_cast**: cast one type to whatever types you like, most dangerous
- * **dynamic_cast**: for type-safe downcasting

26

Usage of *typedef*

❖ *typedef* is used to define a convenient name for any type in C/C++; in many cases, it clarifies the definition

- * *typedef int INT32;* // defines the alias name INT32 for int INT32 var; // is equivalent to int var;
- * *typedef struct tagBook {*
 char author[50];
 char title[50];
} Book; // defines the alias name Book for struct tagBook Book book; // is equivalent to struct tagBook book;
- * *typedef int IntArray[100];* // defines the alias name IntArray IntArray data; // is equivalent to int data[100];
- * *typedef double (*FP)(int, double *);* // defines the alias name FP FP fp; // is equivalent to double (*fp)(int, double *);

Merging these two statements!!

28